



INSTALLATION INSTRUCTIONS

1. Remove any carpeting and all nails and staples
2. Cut off the front of each stair nosing flush to the riser
3. Measure and cut riser using bevel square
4. Apply Construction adhesive to back of riser and fasten firmly (may use finishing nails to hold in place until adhesive sets)
5. Measure and cut first tread to fit
6. Spread a layer of construction adhesive all the way to front of plywood step and apply tread (make sure tread is level and well secured)
7. Install remaining risers and treads following the same pattern
8. (if open sides of stair) Apply endcaps with wood glue, masking tape to hold in place (you may find this easier to do prior to attaching treads, especially if both sides are open). If you would not like to apply tread endcaps you may custom order treads to size with mitre returns (see picture at right)

EASYTREAD SPECS

STOCKED LENGTHS:

42"/48"

STOCKED SPECIES:

RED OAK, MAPLE, WHITE OAK

STOCK SIZE:

3/4" thick with 1-1/2" SQ NOSE


(2-1/2" SQ NOSE available)

OVERALL DEPTH:

11-1/2"

OVERALL LENGTH:

42-1/4" or 48-1/4"



ACCESSORIES:

48" RISER MATERIAL

13" END CAPS for open sides

CUSTOM OPTIONS:

Other sizes and species of wood can be produced.

Custom mitre returns are also available in place of endcaps (see picture below).

